



SC120/30 U LB 55MD ProDrive

DESCRIPTION

Polyurethane inclined lateral profile.

TECHNICAL SPECIFICATIONS

Material	Polyurethane (TPU)		
Hardness	55 ±5 Sh.D		
Colour	Light blue		
Base	Flat		
B Upper base	10.0	mm	0.39 in.
b Bottom base	---	mm	---
H Height	120.0	mm	4.72 in.
Weight	750	gr/m	0.667 oz/in.
Minimum pitch			
longitudinal	---	mm	---
transversal	45	mm	1.8 in.
Minimum pulley diameters ⁽¹⁾			
longitudinal-driving side	---	mm	---
longitudinal-conveying side	---	mm	---
transversal-conveying side	50	mm	2.0 in.
(1) Minimum pulley diameters referred to environment conditions of 20°C			
Temperature resistance ⁽²⁾	min.	-10 °C	14 °F
	max	60 °C	140 °F
(2) Use with limit values may reduce its life			
Roll/bar sizes	0.8 m	2.6 ft	

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments
 EC 1935/2004 Regulation and Amendments
 EC 2023/2006 Regulation and Amendments
 EU 10/2011, 2024/3190 Regulation and Amendments
 FDA (Food and Drug Administration)



METHOD OF APPLICATION

- High frequency welding

NOTES

PRODUCT CODE ES1084

Last Update 30-01-2026

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.