


PROFILES and GUIDES

TECHNICAL DATA SHEET

ES126 T40 RF W CODE **TYPE**

DESCRIPTION

PVC lateral profile, straight flat base without groove.



TECHNICAL SPECIFICATIONS

Material	Polyvir	Polyvinyl chloride (PVC)			
Hardness				60 ±5	Sh.A
Colour				W	/hite
Base					Flat
B Upper base		20.0	mm	0.79	in.
b Bottom base			mm		in.
H Height		40.0	mm	1.57	in.
Weight		377	gr/m	0.335	oz/in.
Minimum pitch					
longitudinal			mm		in.
■ transversal		50	mm	2.0	in.
Minimum pulley diameters ⁽	1)				
longitudinal-driving side			mm		in.
longitudinal-conveying side			mm		in.
■ transversal-conveying signal	80	mm	3.2	in.	
(1) Minimum pulley diameters referred to	environm	nent condition	ons of 2	0°C	
Temperature	min.	-10	°C	14	۰F
resistance ⁽²⁾	max	60	°C	140	۰F
(2) Use with limit values may reduce its li	fe				
Roll/bar sizes		2.4	m	7.9	ft

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments FDA (Food and Drug Administration)

METHOD OF APPLICATION

- High frequency welding
- Hot air welding

NOTES

Last Update: 22-01-2020 Issue: 22-01-2020

DISCLAIMER
The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.