


PROFILES and GUIDES

TECHNICAL DATA SHEET

ES133 T30 RF CODE **TYPE**

DESCRIPTION

PVC lateral profile, straight flat base without groove.



TECHNICAL SPECIFICATIONS

Material			Polyvinyl chloride (PVC)			
Hardness				60 ±5 :	Sh.A	
Colour				Gı	reen	
Base					Flat	
B Upper base		20.0	mm	0.79	in.	
b Bottom base			mm		in.	
H Height		30.0	mm	1.18	in.	
Weight		278	gr/m	0.247	oz/in	
Minimum pitch						
longitudinal			mm		in.	
■ transversal		50	mm	2.0	in.	
Minimum pulley diame	ters ⁽¹⁾					
longitudinal-driving side			mm		in	
longitudinal-conveying side			mm		in	
transversal-conveying side		80	mm	3.2	in	
(1) Minimum pulley diameters refer	red to environn	nent condition	ons of 2	0°C		
Temperature	min.	-10	°C	14	۰F	
resistance (2)	max	60	°C	140	٥F	
(2) Use with limit values may reduce	ce its life					
Roll/bar sizes		2.4	m	7.9	ft	

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments

METHOD OF APPLICATION

- High frequency welding
- Hot air welding

NOTES

Last Update: 22-01-2020 Issue: 22-01-2020

DISCLAIMER
The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.