


CODE ES143
TYPE
T20 U
DESCRIPTION

Polyurethane lateral profile, straight.


TECHNICAL SPECIFICATIONS

Material Polyurethane (TPU)

Hardness 85 ±5 Sh.A

Colour Green

Base Flat

B Upper base 20.0 mm 0.79 in.

b Bottom base --- mm --- in.

H Height 20.0 mm 0.79 in.

Weight 143 gr/m 0.127 oz/in.

Minimum pitch

■ longitudinal --- mm --- in.

■ transversal 45 mm 1.8 in.

Minimum pulley diameters⁽¹⁾

■ longitudinal-driving side --- mm --- in.

■ longitudinal-conveying side --- mm --- in.

■ transversal-conveying side 60 mm 2.4 in.

⁽¹⁾ Minimum pulley diameters referred to environment conditions of 20°C

Temperature resistance ⁽²⁾ min. -20 °C -4 °F

max 70 °C 158 °F

⁽²⁾ Use with limit values may reduce its life

Roll/bar sizes 2.4 m 7.9 ft

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments

METHOD OF APPLICATION

- High frequency welding

NOTES

Issue: 22-01-2020

Last Update: 22-01-2020

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.