


PROFILES and GUIDES

TECHNICAL DATA SHEET

T60 RF W

DESCRIPTION

PVC lateral profile, straight flat base without groove.



COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments FDA (Food and Drug Administration)

TECHNICAL SPECIFICATIONS

Material		Polyvinyl chloride (PVC)			
Hardness				60 ±5	Sh.A
Colour				V	/hite
Base					Flat
B Upper base		20.0	mm	0.79	in.
b Bottom base			mm		in.
H Height		60.0	mm	2.36	in.
Weight		544	gr/m	0.484	oz/in.
Minimum pitch					
longitudinal			mm		in.
transversal		50	mm	2.0	in.
Minimum pulley diameters	$S^{(1)}$				
longitudinal-driving side			mm		in.
longitudinal-conveying side			mm		in.
transversal-conveying side		80	mm	3.2	in.
⁽¹⁾ Minimum pulley diameters referred t	o environm	ent conditio	ons of 2	0°C	
Temperature	min.	-10	°C	14	°F
resistance ⁽²⁾	max	60	°C	140	°F
$^{\left(2\right) }$ Use with limit values may reduce its	life				
Roll/bar sizes		2.4	m	7.9	ft

METHOD OF APPLICATION

- High frequency welding

NOTES	5
-------	---

Last Update 22-01-2020

DISCLAIMER

PRODUCT CODE ES159

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.