


CODE ES160
TYPE
T60 U
DESCRIPTION

Polyurethane, lateral profile, straight.


TECHNICAL SPECIFICATIONS

Material Polyurethane (TPU)

Hardness 85 ±5 Sh.A

Colour Green

Base Flat

B Upper base 20 mm 0.79 in.

b Bottom base --- mm --- in.

H Height 60 mm 2.36 in.

Weight 335 gr/m 0.298 oz/in.

Minimum pitch

■ longitudinal	---	mm	---	in.
■ transversal	45	mm	1.8	in.

 Minimum pulley diameters⁽¹⁾

■ longitudinal-driving side	---	mm	---	in.
■ longitudinal-conveying side	---	mm	---	in.
■ transversal-conveying side	60	mm	2.4	in.

⁽¹⁾ Minimum pulley diameters referred to environment conditions of 20°C

Temperature resistance ⁽²⁾	min.	-20 °C	-4	°F
	max	70 °C	158	°F

⁽²⁾ Use with limit values may reduce its life

Roll/bar sizes 2.4 m 7.9 ft

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments

METHOD OF APPLICATION
NOTES

Issue 22-01-2020

Last Update: 22-01-2020

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.