


CODE ES180
TYPE
S8 P W
DESCRIPTION

Profile fitted transversally or longitudinally.


TECHNICAL SPECIFICATIONS

Material	Polyvinyl chloride (PVC)		
Hardness	60 ±5 Sh.A		
Colour	White		
Base	Flat		
B Upper base	8.0 mm	0.31	<i>in.</i>
b Bottom base	--- mm	---	<i>in.</i>
H Height	8.0 mm	0.31	<i>in.</i>
Weight	83 gr/m	0.074	<i>oz/in.</i>
Minimum pitch			
■ longitudinal	40 mm	1.6	<i>in.</i>
■ transversal	40 mm	1.6	<i>in.</i>
Minimum pulley diameters ⁽¹⁾			
■ longitudinal-driving side	80 mm	3.2	<i>in.</i>
■ longitudinal-conveying side	130 mm	5.1	<i>in.</i>
■ transversal-conveying side	50 mm	2.0	<i>in.</i>
⁽¹⁾ Minimum pulley diameters referred to environment conditions of 20°C			
Temperature resistance ⁽²⁾	min.	-10 °C	14 °F
	max	60 °C	140 °F
⁽²⁾ Use with limit values may reduce its life			
Roll/bar sizes	200.0 m	656.0	<i>ft</i>

COMPLIANCES

 REACH EC 1907/2006 Regulation and Amendments
 FDA (Food and Drug Administration)

METHOD OF APPLICATION

- Hot air welding
- High frequency welding

NOTES

Issue: 22-01-2020

Last Update: 22-01-2020

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.