

## **POLYURETHANE ROUND BELTS**

### **TECHNICAL DATA SHEET**

code ES206	TYPE	PU A 13x8
------------	------	-----------

COMPOSITION	
Material	Thermoplastic polyurethane (TPU)
Hardness	92 ±5 Sh.A
Colour	Green
Surface	Smooth
Coefficient of friction on steel	0.4



# TECHNICAL SPECIFICATIONS

Diameter			mm		in.
Weight		gr/m		lbs./ft.	
Minimum pulley diameter		60.0	mm	2.36	in.
Pull for 8% elongation		45.0	N	10.1	lbf.
Temperature resistance (1) (1) Use of the belt with limit	min. max t values r		°C	-4 140	°F
Humidity influence				no	
Permanent antistatic dynamically UNI EN ISO 21179 no					

#### FEATURES

- Extremely good tensile strengths
- Elasticity
- Flexibility values

## COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments FDA (Food and Drug Administration)

## SUITABLE FOR

Packaging

#### JOINTING SYSTEM

Being thermoweldable polyurethane it enables quick endless jointing of belts. For high precision joints of V-belts of any size CHIORINO supply the **FAST JOINT welder "S15".** 

## NOTES

Belts which are used in various markets for transmission of light duty drives, at medium low speeds and conveying light loads.

Issue: 01-02-2019 Last Update: 1-02-2019

#### DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.