

CODE ES22	24		ТҮРЕ	RU-15
COMPOSITION				
Material	Thermoplastic poly	urethane (TPU)		
Hardness	92 ±5 Sh.A			
Colour	Green			
Surface	Rough			
Coefficient of friction on steel	0.4			
TECHNICAL SPECI	FICATIONS		FEATURES	
Diameter	15.0 mm	0.59 in.	 Extremely good tensile Elasticity 	strengths
Weight	210.0 gr/m	0.14 lbs./ft.	- Flexibility values	
Minimum pulley dia	meter 130.0 _{mm}	5.12 in.	COMPLIANCES	
Pull for 8% elongati	on 440.0 N	98.9 lbf.	REACH EC 1907/2006 Regu	lation and Amendments
Femperature resistance (1) 1) Use of the belt with lin	min20 °C max 60 °C nit values may reduce its lifu	-4 °F 140 °F		
Humidity influence		no		
Permanent antistati JNI EN ISO 21179	c dynamically	no	SUITABLE FOR Packaging Printing and graphic Corrugated carton: punc	hing & creasing
JOINTING SYSTEM			NOTES	
endless jointing of	ble polyurethane it belts. For high prec size CHIORINO sup 5".	ision joints of	Belts which are use transmission of light dut and conveying light load	y drives, at medium low speed
			T	