


CODE	ES33		TYPE	KN17	
<b>DESCRIPTION</b>					
Knotched profile can be used on smaller roller diameters.					
<b>TECHNICAL SPECIFICATIONS</b>					
Material	Polyvinyl chloride (PVC)				
Hardness	60 ±5 Sh.A				
Colour	Green				
Base	Grooved				
B Upper base	17.0 mm	0.67	in.		
b Bottom base	9.0 mm	0.35	in.		
H Height	11.0 mm	0.43	in.		
Weight	141 gr/m	0.125	oz/in.		
Minimum pitch					
■ longitudinal	45 mm	1.8	in.		
■ transversal	45 mm	1.8	in.		
Minimum pulley diameters <sup>(1)</sup>					
■ longitudinal-driving side	100 mm	3.9	in.		
■ longitudinal-conveying side	160 mm	6.3	in.		
■ transversal-conveying side	---	---	in.		
<sup>(1)</sup> Minimum pulley diameters referred to environment conditions of 20°C					
Temperature resistance <sup>(2)</sup>					
	min.	-10 °C	14	°F	
	max	60 °C	140	°F	
<sup>(2)</sup> Use with limit values may reduce its life					
Roll/bar sizes	100.0 m	328.0	ft		
<b>COMPLIANCES</b>					
REACH EC 1907/2006 Regulation and Amendments					
<b>METHOD OF APPLICATION</b>					
<ul style="list-style-type: none"> <li>- Hot air welding</li> <li>- High frequency welding</li> </ul>					
<b>NOTES</b>					



Issue: 22-01-2020

Last Update: 22-01-2020

**DISCLAIMER**

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.