

ROFILES and GUIDES				TECHNICAL DATA SHEET	
DDE ES71 TYP		TYPE	L20 RF		
DESCRIPTION					
PVC inclined lateral profile, flat l	base withou	t groove.			B
TECHNICAL SPECIFICATIONS					d American days sucks
Material	Polyvinyl	chloride (P	VC)	ACH EC 1907/2006 Regulation an	a Amenaments
Hardness		60 ±5 3	Sh.A		
Colour		G	reen		
Base			Flat		
3 Upper base	20.0 mm	0.79	in.		
o Bottom base	mn	ı	in.		
H Height	20.0 mm	n 0.79	in.	High frequency welding	
Weight	211 gr/	m <b>0.188</b>	oz/in.		
1 Inimum pitch					
longitudinal transversal	mm 50 mm		in.	NOTES	
1 Minimum pulley diameters <sup>(1)</sup>					
longitudinal-driving side	mn		in.		
longitudinal-conveying side	mn		in.		
transversal-conveying side	80 mm	n 3.2	in.		
<sup>1)</sup> Minimum pulley diameters referred to environ	ment conditions o	20°C			
Temperature min. resistance <sup>(2)</sup>		14	°F		
IIIdA	60 °C	140	°F		
<sup>(2)</sup> Use with limit values may reduce its life					
	<b>2.4</b> m	7.9	ft		
Roll/bar sizes					

DISCLAIMER The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.

CHIORINO S.p.A. - VIA S. AGATA, 9 - 13900 BIELLA - ITALIA - P.O.B. 460 - TEL. +39-015-8489.1 - FAX +39-015.8489161 chiorino@chiorino.com