



CODE ES94

TYPE
S12 U P
DESCRIPTION

Profile fitted transversally or longitudinally.


TECHNICAL SPECIFICATIONS

Material Polyurethane (TPU)

Hardness 85 ±5 Sh.A

Colour Green

Base Flat

B Upper base 12 mm 0.47 in.

b Bottom base --- mm --- in.

H Height 12 mm 0.47 in.

Weight 146 gr/m 0.130 oz/in.

Minimum pitch

| | | |
|----------------|-------|---------|
| ■ longitudinal | 45 mm | 1.8 in. |
| ■ transversal | 45 mm | 1.8 in. |

 Minimum pulley diameters⁽¹⁾

| | | |
|-------------------------------|--------|---------|
| ■ longitudinal-driving side | 100 mm | 3.9 in. |
| ■ longitudinal-conveying side | 160 mm | 6.3 in. |
| ■ transversal-conveying side | 80 mm | 3.2 in. |

⁽¹⁾ Minimum pulley diameters referred to environment conditions of 20°C

| | | | |
|---------------------------------------|------|--------|--------|
| Temperature resistance ⁽²⁾ | min. | -20 °C | -4 °F |
| | max | 70 °C | 158 °F |

⁽²⁾ Use with limit values may reduce its life

Roll/bar sizes 100.0 m 328.0 ft

COMPLIANCES

 REACH EC 1907/2006 Regulation and Amendments
 FDA (Food and Drug Administration)

METHOD OF APPLICATION

- Hot air welding
- High frequency welding

NOTES

Issue 22-01-2020

Last Update: 22-01-2020

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.