



CODE	ES95		TYPE	S12 U P W	
DESCRIPTION					
Profile fitted transversally or longitudinally.					
TECHNICAL SPECIFICATIONS					
Material	Polyurethane (TPU)				
Hardness	70 ±5 Sh.A				
Colour	White				
Base	Flat				
B Upper base	12.0 mm	0.47	in.		
b Bottom base	---	---	in.		
H Height	12.0 mm	0.47	in.		
Weight	210 gr/m	0.187	oz/in.		
Minimum pitch					
■ longitudinal	45 mm	1.8	in.		
■ transversal	45 mm	1.8	in.		
Minimum pulley diameters ⁽¹⁾					
■ longitudinal-driving side	100 mm	3.9	in.		
■ longitudinal-conveying side	160 mm	6.3	in.		
■ transversal-conveying side	80 mm	3.2	in.		
⁽¹⁾ Minimum pulley diameters referred to environment conditions of 20°C					
Temperature resistance ⁽²⁾					
	min.	-20 °C	-4	°F	
	max	70 °C	158	°F	
⁽²⁾ Use with limit values may reduce its life					
Roll/bar sizes	100.0 m	328.0	ft		
COMPLIANCES					
REACH EC 1907/2006 Regulation and Amendments EC 1935/2004 Regulation and Amendments EC 2023/2006 Regulation and Amendments EU 10/2011, 2017/752 Regulation and Amendments HACCP (Hazard Analysis and Critical Control Points) FDA (Food and Drug Administration)					
METHOD OF APPLICATION					
- Hot air welding - High frequency welding					
NOTES					



Issue: 22-01-2020

Last Update: 27-05-2021

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.