


TECHNICAL DATA SHEET

| CODE | LA-89 | | ٦ | | | | |
|--------------------------|-------|---|---|--|--|--|--|
| | | | | | | | |
| COMPOSITION | | | | | | | |
| Material | | Natural elastomer (NR)/thermoplastic compound | | | | | |
| Colour | | Purple red | | | | | |
| Hardness | | 40 ± 5 Sh.A | | | | | |
| Outer surface pat | tern | FL | | | | | |
| Inner surface pattern | | Smooth | | | | | |



X-Weld[™]

TECHNICAL SPECIFICATIONS

| Total thickness | 6.3 | ± 0,20 | mm | 0.25 ± 0.008 | in. |
|----------------------------|-------|--------|-------|--------------|------------|
| Weight | 7.2 : | ± 0,20 | kg/m² | 1.47 ± 0.008 | lbs./sq.ft |
| Production width | | 1200 | mm | 47 | in. |
| Temperature resistance (1) | min. | -20 | °C | -4 | °F |
| resistance (1) | max. | +80 | °C | 176 | °F |

(1) use of the sheeting with limit values may reduce its life

COMPLIANCES REACH Regulation EC 1907/2006 and amendments SUITABLE FOR Packaging Ceramic industry Wood industry

Issue:

29-06-2015

Last Update 23-06-2016

DISCLAIMER The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.