


CODE NA1269
TYPE
ME 30/20 blue DET
TECHNICAL SPECIFICATIONS

Mesh material	PET monofilament	
Guides and profiles material	DET® Polyurethane (TPU)	
Colour	Blue	
Mesh opening	3000 µm	56.3 %
Mesh thickness	2.00 mm	0.08 in.
Mesh weight	0.60 kg/m ²	0.12 lbs./sq.ft
Minimum diameter ⁽¹⁾		
■ Bending roller	80 mm	3.15 in.
■ Counter-bending roller	80 mm	3.15 in.
⁽¹⁾ The above mentioned values depend on the type of Chiorino joint recommended.		
Temperature resistance ⁽²⁾	min. -15 °C	5 °F
	max. 70 °C	158 °F
⁽²⁾ Use of the belt with limit values may reduce its life.		
Edge standard width	40 mm	2 in.
Max. production width	5000 mm	197 in.

SUITABLE FOR

Fruits and vegetables
Food: dairy

NOTES

FEATURES

Humidity influence	no
Suitable to metal detector	no
Permanent antistatic dynamically (UNI EN ISO 21179)	no
Static conductivity (UNI EN ISO 284)	no
Conveying on skid bed	yes
Conveying on rollers	yes
Conveying on skid bed on top and return	yes
Troughed conveying	no
Swan neck conveying	no
Inclined conveying	no
Accumulators belts	yes
Curved conveyor	no
Chemical resistances link	12

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments
EC 1935/2004 Regulation and Amendments
EC 2023/2006 Regulation and Amendments
EU 10/2011, 2017/752 Regulation and Amendments
FDA (Food and Drug Administration)



Issue: 10-09-2020

Last Update: 10-09-2020

DISCLAIMER

The information contained in this document describes the features of the Chiorino product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the Chiorino product. Chiorino cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.