


CODE NA-1482F_D6

TYPE
Compact Minidrive 15/20 A blue DET
COMPOSITION


FEATURES

Humidity influence	no
Suitable to metal detector	no
Permanent antistatic dynamically (UNI EN ISO 21179)	no
Static conductivity (UNI EN ISO 284)	no
C.I.P. (Clean In Place)	yes
Conveying on plastic strips UHMW ⁽²⁾	yes
Conveying on rollers	yes
Troughed conveying	no
Swan neck conveying	no
Inclined conveying	no
Accumulators belts	no
Curved conveyor	no
Chemical resistances link	12

Description Compact belt with traction core treated to avoid waving, timing profile on the drive side

Material Polyurethane (TPU)

Thickness 1.50 mm 0.06 in.

Weight 1.70 kg/m² + 0.11 kg/m (for row of teeth)
0.35 lbs./sq.ft + 0.07 lbs./ft (for row of teeth)

Surface pattern Smooth

Colour Dark blue

Coefficient of friction MF

TECHNICAL SPECIFICATIONS

Elongation at 1% 10 N/mm 57 lbs./in.

Pitch 20 ± 0.4 mm 0.79 ± 0.16 in.

Temperature resistance⁽²⁾ min. -30 °C -22 °F
max. +90 °C 194 °F

⁽¹⁾ Use of the belt with limit values may reduce its life

Max. production width 800 mm 31 in.

Minimum roller diameter:

- Bending roller 20 mm 0.8 in.
- Counter-bending roller 50 mm 2.0 in.

Coefficient of friction:

- Stainless steel - dry/wet 0.50/0.42 [-]
- UHMW⁽²⁾ - dry/wet 0.42/0.35 [-]

⁽²⁾UHMW = Ultra High Molecular Weight

COMPLIANCE

REACH EC 1907/2006 Regulation and Amendments
EC 1935/2004 Regulation and Amendments
EC 2023/2006 Regulation and Amendments
EU 10/2011, 2017/752 Regulation and Amendments
HACCP (Hazard Analysis and Critical Control Points)
FDA (Food and Drug Administration)


SUITABLE FOR

Food industry
Packaging

NOTES

Issue: 13-07-2018

Last Update: 17-12-2018

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.