



CONVEYOR AND PROCESS BELTS

TECHNICAL DATA SHEET


CODE		NA1717		TYPE		1DM8 U0-U2 HP W A AM	
COMPOSITION							
Conveying surface	Material	Polyurethane (TPU) - HP® system					
	Thickness	0.20	mm	0.008	in.		
	Surface pattern	Smooth					
	Colour	White					
	Coefficient of friction	MF					
Textile carcass	Material	Polyester (PET) - HP® system					
	Plies no.	1					
	Weft type	Double weft rigid					
Driving surface	Material	Fabric polyurethane (TPU) impregn. - HP® system					
	Thickness	---	mm	---	in.		
	Surface pattern	Fabric					
	Colour	Light blue					
TECHNICAL SPECIFICATIONS							
Total thickness		1.35	mm	0.05	in.		
Weight		1.40	kg/m²	0.29	lbs./sq.ft		
Elongation at 1%		8	N/mm	46.0	lbs./in.		
Max. admissible pull		16	N/mm	91.0	lbs./in.		
Temperature resistance ⁽¹⁾	min.	-30	°C	-22	°F		
	max.	110	°C	230	°F		
⁽¹⁾ Use of the belt with limit values may reduce its life.							
Minimum radius / diameter ⁽²⁾							
■ Knife edge minimum radius		4	mm	0,16	in.		
■ Bending roller min. diameter		8	mm	0.31	in.		
■ Counter-bending roller min. diameter		16	mm	0.63	in.		
⁽²⁾ The above mentioned values depend on the type of CHIORINO joint recommended.							
Coefficient of friction on driving surface							
■ Raw steel sheet		0.20	[-]				
■ Laminated plastic/wood		0.25	[-]				
■ Steel roller		0.20	[-]				
■ Rubberized roller		0.30	[-]				
Max. production width		2100	mm	83	in.		
SUITABLE FOR							
Food: chocolate cooling tunnel							
Food: bakery							
Food: biscuits and crackers							
Food: dairy							
Food: slicing machines							
Food: seafood processing							
Pharmaceutics industry							
Packaging							



PRODUCT SYSTEM 

FEATURES	
Humidity influence	no
Suitable to metal detector	yes
Permanent antistatic dynamically (UNI EN ISO 21179)	yes
Static conductivity (UNI EN ISO 284)	no
Conveying on skid bed	yes
Conveying on rollers	yes
Conveying on skid bed on top and return	no
Troughed conveying	no
Swan neck conveying	no
Inclined conveying	yes
Accumulators belts	no
Curved conveyor	no
Chemical resistances link	12

COMPLIANCES	
REACH EC 1907/2006 Regulation and Amendments	
EC 1935/2004 Regulation and Amendments	
EC 2023/2006 Regulation and Amendments	
EU 10/2011, 2023/1442 Regulation and Amendments	
HACCP (Hazard Analysis and Critical Control Points)	
FDA (Food and Drug Administration)	
VEGAN	



NOTES	
-------	--



PRODUCT SYSTEM **HP[®] AM**

FEATURES

Humidity influence	no
Suitable to metal detector	yes
Permanent antistatic dynamically (UNI EN ISO 21179)	yes
Static conductivity (UNI EN ISO 284)	no
Conveying on skid bed	yes
Conveying on rollers	yes
Conveying on skid bed on top and return	no
Troughed conveying	no
Swan neck conveying	no
Inclined conveying	yes
Accumulators belts	no
Curved conveyor	no
Chemical resistances link	12

COMPLIANCES

REACH EC 1907/2006 Regulation and Amendments
 EC 1935/2004 Regulation and Amendments
 EC 2023/2006 Regulation and Amendments
 EU 10/2011, 2023/1442 Regulation and Amendments
 HACCP (Hazard Analysis and Critical Control Points)
 FDA (Food and Drug Administration)
 VEGAN



NOTES


Issue: 10-01-2023

Last Update: 25-09-2023

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.

CHIORINO S.p.A. - VIA S. AGATA, 9 - 13900 BIELLA - ITALIA - P.O.B. 460 - TEL. +39-015-8489.1 - FAX +39-015.8489161
 chiorino@chiorino.com - www.chiorino.com


CODE NA1717
TYPE
1DM8 U0-U2 HP W A AM
Recommended joining procedure
SINGLE Z - 80 x 10 mm
Other joining methods can be used:

**A = 80 mm
B = 10 mm**

Check our general catalogue to get further info on CHIORINO joining methods.


• Pressing
Heating press P \ PL \ PLS

Press settings	
Upper platen temperature	150 °C
Lower platen temperature	150 °C
Temperature gauge setting	150 °C
Curing time in press	4 min.
Pressure	2,5 bar
Film	TC740 - Film PU HP W AM
Cement	---

1. Use the KM330 thermometer to check the effective temperature inside the belt. Place the thermometer gauge as shown by the drawing at side.



2. Allow the cooling cycle to be completed before removing the belt from the press.
3. A reliable strength of the joint is ensured, providing that temperatures reached by the press are those indicated in the table at side. A periodical inspection of the thermostats is recommended, to make sure they function correctly.

• Layout of components

• Notes

Issued: 13-01-2023

Last Update: 11-07-2023

DISCLAIMER

The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.