

| CODE NA1724A | | TYPE | | HP Compact 15 blue AM | | | | | |
|--|--|---------------|-------------|---|--|-----|--|--|--|
| COMPOSITION | | | | FEATURES | | | | | |
| | | | | Humidity influence | | no | | | |
| | | | | Suitable to metal detector | | yes | | | |
| | | | | Permanent antistatic dynamically (UNI EN ISO 21179) | | no | | | |
| | | | | Static conductivity (UNI EN ISO 284) | | no | | | |
| | | | | C.I.P. (Clean In Place) | | yes | | | |
| | | | | Conveying on plastic strips UHMW ⁽²⁾ | | yes | | | |
| | | | | Conveying on rollers | | yes | | | |
| | | | | Troughed conveying | | yes | | | |
| | | | | Swan neck conveying | | no | | | |
| | | | | Inclined conveying | | no | | | |
| | | | | Accumulators belts | | no | | | |
| | | | | Curved conveyor | | yes | | | |
| | | | | Chemical resistances link | | 12 | | | |
| | | | | COMPLIANCE | | | | | |
| | | | | REACH EC 1907/2006 Regulation and Amendments | | | | | |
| EC 1935/2004 Regulation and Amendments | | | | | | | | | |
| EC 2023/2006 Regulation and Amendments | | | | | | | | | |
| EU 10/2011, 2023/1442 Regulation and Amendments | | | | | | | | | |
| HACCP (Hazard Analysis and Critical Control Points) | | | | | | | | | |
| FDA (Food and Drug Administration) | | | | | | | | | |
| TECHNICAL SPECIFICATIONS | | | | SUITABLE FOR | | | | | |
| Elongation at 1% | | 5 N/mm | 29 lbs./in. | Food industry | | | | | |
| Temperature resistance ⁽¹⁾ | | min. -30 °C | -22 °F | Packaging | | | | | |
| | | max. +110 °C | 230 °F | | | | | | |
| ⁽¹⁾ use of the belt with limit values may reduce its life | | | | | | | | | |
| Max. production width | | 2000 mm | 79 in. | | | | | | |
| Minimum roller diameter: | | | | | | | | | |
| ■ Bending roller | | 25 mm | 1.0 in. | | | | | | |
| ■ Counter-bending roller | | 60 mm | 2.4 in. | | | | | | |
| Coefficient of friction: | | | | | | | | | |
| ■ Stainless steel - dry/wet | | 0.50/0.42 [-] | | | | | | | |
| ■ UHMW ⁽²⁾ - dry/wet | | 0.42/0.35 [-] | | | | | | | |
| ⁽²⁾ UHMW = Ultra High Molecular Weight | | | | | | | | | |
| PRODUCT CODE NA1724A | | | | Last Update: 13-09-2023 | | | | | |
| DISCLAIMER | | | | | | | | | |
| The information contained in this document describes the features of the CHIORINO product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the CHIORINO product. CHIORINO cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice. | | | | | | | | | |