

| TEXGUM" ROLLER COVERINGS           |                          |                              |          |            | TECHNICAL DATA SHEE |   |
|------------------------------------|--------------------------|------------------------------|----------|------------|---------------------|---|
| CODE TX170                         |                          |                              |          |            | ТҮРЕ                | SG0-E nc  |
|                                    |                          |                              |          |            |                     |   |
| STRUCTURE                          |                          |                              |          |            |                     |   |
| External covering                  | I                        |                              |          |            |                     |   |
| Material                           | Synthe                   | tic elastomer                |          |            |                     |   |
| Surface pattern                    | Porous and grinded       |                              |          |            |                     |   |
| Special execution                  | Foam synthetic elastomer |                              |          |            |                     |   |
| Colour                             | Hazelnut                 |                              |          |            |                     | ~~~~~   |
| Hardness                           | 40 ±5 Sh.A               |                              |          |            |                     |   |
| <b>Textile carcass</b><br>Material | Polyest                  | er (PET)                     |          |            |                     |   |
| TECHNICAL SPEC                     |                          | IS                           |          |            | ADHES               | SIVES   |
| Total thickness                    |                          | 2.7 mm                       | 0.11     | in.        |                     | the covering to the roller it is recommend<br>ingle-component adhesive TEXCOL CHIOR |
| Weight                             |                          | <b>2.2</b> kg/m <sup>2</sup> | 0.45     | lbs./sq.ft |                     |   |
| Tensile strength                   |                          | 60 N/mm                      | 343      | lbs./in.   | EEATI               | IDES  |
| Temperature                        | min                      | -10 °C                       | 14       | °F         | FEATU               |   |
| resistance (1)                     | max                      | 120 °C                       | 248      | °F         | - Good sh           | ock-absorption properties   |
| (1) Use of the roller c            | overing with             | n limit values m             | ay reduc | e its life |                     |   |
| ROLL SIZES                         |                          |                              |          |            | COMP                | LIANCES   |
| Length                             |                          | 115 m                        | 4528     | in.        |                     | egulation EC 1907/2006 and amendments   |
| Width (2)                          |                          | 50 mm                        | 2        | in.        |                     |   |
| (2) Other widths upor              | n request                | 70 mm                        | 3        | in.        |                     |   |
| SUITABLE FOR                       |                          |                              |          |            | NOTES               | 8   |
| Textile: weaving                   |                          |                              |          |            |                     |   |
|                                    |                          |                              |          |            |                     |   |

The information contained in this document describes the features of the Chiorino product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the Chiorino product. Chiorino cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.