

EXGUM" ROL	LER CC	VERINGS		TECHNICAL DATA SHEET		
CODE TX5	5				ТҮРЕ	SG7
STRUCTURE						
External covering		tio olootomon				
Material	Synthe	tic elastomer				
Surface pattern						
Special execution						Press of the second sec
Colour	White					
Hardness	65 ±5 9	Sh A				
	05 -5 3					
Textile carcass						/
Material	Polyest	er (PET)				$\circ \circ \circ \circ \circ \circ$
TECHNICAL SPEC		IS			AD	IESIVES
Total thickness		2.0 mm	0.08	in.		ue the covering to the roller it is recommendable e single-component adhesive TEXCOL CHIORING
Weight		2.2 kg/m ²	0.45	lbs./sq.ft		
Tensile strength		60 N/mm	343	lbs./in.		
Temperature	min	-10 °C	14	°F		ATURES
resistance (1)	max	120 °C	248	°F		l adhesion
(1) Use of the roller c	overing wit	h limit values m	ay reduc	e its life	- Resis	stance to oils
ROLL SIZES						
Length		115 m	4528	in	CO	MPLIANCES
Width (2)					REACH	Regulation EC 1907/2006 and amendments
wiuur (<i>2)</i>		50 mm 70 mm		in. in.		
(2) Other widths upor	n request					
SUITABLE FOR					NO	TES
Textile: weaving					Self-ad	dhesive/A version available
Issue: 26-09-2006					1	Last Update: 2-1-2018

The information contained in this document describes the features of the Chiorino product as tested in a laboratory environment at a temperature of +23 degrees °C at 50% relative humidity. It does not necessarily reflect the conditions of industrial use and it does not guarantee the product to be suitable for certain applications. The client remains liable for the proper selection and correct use of the Chiorino product. Chiorino cannot be held responsible should damages arise from the use of its products. Necessary alterations to this data can be made without prior notice.